CURWE Main Display



Customizable display view with supported Windows True Type fonts.

Desktop, ceiling or wall installation options

WiFi IEEE 802.11 Communication option

Ultra-Red Matrix led display technolo

48x10 pixel resolution.

Scrolling text options.

Power LED Technology, 2200mcd luminance

PALIFR

Thanks to SMT dot-matrix Power LED production technology, for preferring different colors without any additional cost up to 2200mcd luminance.

EIA RS485, 1200m cable communication



By means of athe developed superior communication technology, you can operate with cable up to 1200 meters with integrated EIA RS485 hardwares and special communication protocol.

Working in any place, any time, any surface



With the programmability feature, you can easily use the displays in different part of your corporation (Counter number can be changed in any way) and use on ceil, floor or desktop.

Enjoy the infinite flexiblity in your WiFi wireless network with Curwe main displays with your queue systems. Curwe main displays is fully compatible with the standart IEEE 802.11 WiFi network hardwares such as router, modem or access points. Curwe displays is working with only one static or DCHP IP address and which can displays up to 20 previous call with one connection. It provides a perfect wireless working experience up to 300m. It works any point in your office, just like smartphone or tablet computer, at any time, without the need for cabling or renovations. It can be installed on ceiling, wall or desktop with several installation brackets.

WiFi IEEE 802.11 Wireless Communication



It operates compatibly with all WiFi consumer products like Modems, Routers or Access Points to connect your corporate/personel wireless or ethernet networks.



Technical Specifications

General Properties Resolution: 48x10px

LED-Technology: Power Led Matrix Display LED-Colors: Red, White, Blue Chasis color: Eloxal Call number rows: 1 Additional row: Yes (Up to 20)

Functional Properties

Central clock: Optional Ticket number character size: 4 Ticket number Prefix: Yes Counter number character size: 2 Directions arrow: Yes Video display: N/A Image/Slide show display: N/A Special text instead of ticket number: No Special text instead of counter number: No . Previous call number display: Yes Next call number display: Yes Melody option: Yes Corporate melody option: Yes Volume control: Yes

Hardware Properties Network: RS485 Full Duplex (WiFi Optional) Technology: Power Matrix Lec Connection: RJ11 or WiFi Operating voltage: 12V DC Power consumption: 20W (2rows) Weight: 1950g (2rows) Dimensions [mm] (WxDxH): 410x33x255 (2Rows) Warranty: 2 Years (Ext. Warranty Ontional Luminance (per led): 500mcd (2200 for White)

API-Support

Ticket Call: Yes Scrolling text: Yes





