CARACTERIA CONTRACTOR OF CONT

Routing Display

Convert your Monitors or TVs into queue management system routing displays with Qsmart DSI. The screens with O-smart DSI connecting to your queue

> management system with Ethernet or Wireless network infrastructure. It turn into the corporate TV which broadcast advertisement, make TV broadcasting, display your announcements and show your videos or photographs instead of the static LED screens. You can display the live RSS services and you can ensure that your customers follow up your screens with the live weather forecasts or several different type of live services.

- Semi-Transparent full screen warning attracting the attention in the ticket call.
- MPEG, MPEG4, AVI, 3GP video codec, BMP, GIF, JPEG, JPG, PNG image formats support.
- WiFi or Gigabit Ethernet Network connection.

Interactive interaction with your customers with the several options such as QR code, scrolling text, flash news, RSS.



Ethernet or WiFi

DSI can work on the local networks with WiFi or Gigabit Ethernet or on the GSM networks with 3G modem. You can eliminate the distance dependency between your routing displays and your queue management system.

4K Ultra HD display quality

DSI provides 4K Ultra HD image quality with its powerful 4-core processor and external GPU. Your videos and images are displayed as in the real life at 4K quality.



With the integrated RSS services, it displays the weather forecast, sports, agenda, astrology, technology, automobile news and foreign exchange rates as live.

Special build of Android OS

With specifically designed operating system, the problems which you are used to from computers such as virus infection, system crash are invalid. It is perfectly designed to process multimedia. It is not a computer.

It supports the popular videos and pictures format



Technical Specifications

General Properties Resolution: 4K Ultra HD LED-Technology: N/A LED-Colors: N/A Chasis color: Black Call number rows: 1,2,3,4 or 8 Additional row: No

Functional Properties Scrolling text: Yes Central clock: Yes Ticket number character size: 4 Ticket number Prefix: Yes Counter number character size: 2 Directions arrow: Yes Video display: Yes(Live broadcast with RTSP) Image/Slide show display: Yes Special text instead of ticket number: Yes Special text instead of counter number: Yes Previous call number display: Yes Next call number display: Yes Melody option: Yes Corporate melody option: No Volume control: Yes



Network: Ethernet / WiFi (Optional) Technology: Android OS 4.2.2 Connection: RJ45 / WiFi Operating voltage: 5V DC Power consumption: 2.5W Weight: 266g Dimensions [mm] (WxDxH): 135x85x40 Warranty: 2 Years (Ext.warranty Optional)

API-Support Ticket Call: Yes Scrolling text: Yes





Display up to 8 previous calls. 2, 3, 4 or 8 previous call row

Semi-transparent, full screen warning show on the main video

Full screen warning attracting the attention

Central clock, service or information display

Main Routing Display

Nummer

8 row support

attracting the attention.

in the form of scrolling text.

usades.

volume.

Numme

603

61010

2

2

Platz

2







4K











www.qsmart.com.tr (info@qsmart.com.tr

broadcast.